

View Online at <https://aerobasegroup.com/nsn/4320-00-326-2434>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

103.3 gallons per minute

Total Head:

5.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Width:

15.0000 inches

Unpackaged Unit Height:

41.000 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.2

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

W/ float activated switch

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400