## NSN 4320-00-327-8620

**Mounting Type:** 

Bulk Transfer Flammable Liquid Pumping Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-327-8620

Mounting Type.
Trailer
Discharge Connection Flange Thickness:
Any acceptable
Prime Mover Horsepower Rating:
77.000
Prime Mover Type:
Diesel engine
Manufacturer Name:
Coach and car equipment corp
Manufacturer Identifying Number:
5060305
Discharge Connection Type:
Flanged
Capacity Rating:
600.0 gallons per minute
Suction Connection Type:
Flanged
Pump Type:
Centrifugal
Pump Manufacturer Name:
Barnes mfg co
Pump Manufacturer Identifying Number:
52607sa
Suction Connection Flange Type:
Drilled
Suction Connection Flange Thickness:
Any acceptable
Suction Connection Flange Bolt Circle Diameter:
9.500 inches
Suction Connection Flange Bolt Hole Quantity:
8
Suction Connection Flange Bolt Hole Diameter:
0.750 inches
Discharge Connection Flange Bolt Circle Diameter:
9.500 inches
Discharge Connection Flange Bolt Hole Quantity:
8
Discharge Connection Flange Bolt Hole Diameter:
0.750 inches
Explosion Proof Feature:
Not included

## NSN 4320-00-327-8620

Bulk Transfer Flammable Liquid Pumping Assembly - Page 2 of 2



Engine Manufacturer Code:
24144
Discharge Connection Flange Type:
Drilled
Engine Manufacturer Identifying Number:
52744
Ground Cable:
Included
Cable Reel:
Not included
Water Remover Type:
Strainer
Drum Emptying Manifold Assembly:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T103-m