## NSN 4320-00-340-1599

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-340-1599

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Current Type:
Ac
Media For Which Designed:
Water, fresh
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
2100.0 gallons per minute
Discharge Pressure:
41.0 pounds per square inch gage
Total Head:
94.000 feet
Operating Speed At Rated Capacity:
1185.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Radial flow
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Current Rating In Amps:
97.0
Prime Mover Power Rating:
75.000 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
00.0

60.0

## NSN 4320-00-340-1599

Centrifugal Pump Unit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400