

View Online at <https://aerobasegroup.com/nsn/4320-00-351-7419>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

16.3 gallons per minute

Discharge Pressure:

14.0 pounds per square inch gage

Total Head:

27.000 feet

Operating Speed At Rated Capacity:

3200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

9.125 inches

Unpackaged Unit Width:

4.5000 inches

Unpackaged Unit Height:

6.188 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

2.2

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Prime Mover Power Rating:

0.125 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400