## NSN 4320-00-355-7362

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-355-7362

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Trailer
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Maximum Discharge Flow Rate:
1000.0 gallons per minute
Total Head:
80.000 feet
Suction Lift:
10.000 feet
Operating Speed At Rated Capacity:
160.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Gasoline engine
Discharge Connection Thread Size And Series/type Designator:
6.000-8 npt
Intake Connection Thread Size And Series/type Designator:
6 000-8 npt

6.000-8 npt

## NSN 4320-00-355-7362

Centrifugal Pump Unit - Page 2 of 2



Featui	rae I	Dro	wic	امطا	ŀ
reatui	25	-10	vic	eО	١.

Self-priming

**Prime Mover Power Rating:** 

30.000 horsepower

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A19400