## NSN 4320-00-360-1138

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-360-1138

| Prime Mover Quantity:                   |
|---|
| 1                                       |
| Prime Mover Cooling Medium:             |
| Air                                     |
| Stage Quantity:                         |
| 1                                       |
| Intake Connection Quantity:             |
| 1                                       |
| Intake Connection Type:                 |
| Round flange                            |
| Discharge Connection Quantity:          |
| 1                                       |
| Discharge Connection Type:              |
| Round flange                            |
| Current Type:                           |
| Ac                                      |
| Media For Which Designed:               |
| Water, salt                             |
| Environmental Protection:               |
| Dripproof                               |
| Pump Quantity:                          |
| 1                                       |
| Cooling Method:                         |
| Self ventilated                         |
| Maximum Discharge Flow Rate:            |
| 1040.0 gallons per minute               |
| Total Head:                             |
| 30.000 feet                             |
| Operating Speed At Rated Capacity:      |
| 1160.0 revolutions per minute           |
| Pumping Element Operating Position:     |
| Vertical                                |
| Centrifugal Pump Design:                |
| Radial flow                             |
| Centrifugal Pump Impeller Quantity:     |
| 1                                       |
| Centrifugal Pump Impeller Suction Type: |
| Double                                  |
| Prime Mover Type:                       |
| Electric motor                          |
| Inclosure Type:                         |
| Partially enclosed                      |

## **NSN 4320-00-360-1138**Centrifugal Pump Unit - Page 2 of 2



| Current Rating In Amps:   |
|---------------------------|
| 17.0                      |
| Prime Mover Power Rating: |
| 12.500 horsepower         |
| Voltage In Volts:         |
| 440.0                     |
| Phase:                    |
| Three                     |
| Special Features:         |
| Provided w/controller     |
| Frequency In Hertz:       |
| 60.0                      |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
| -                         |
| Demilitarization:         |
| No                        |
| Fiig:                     |
| Δ19400                    |