NSN 4320-00-360-1639

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-360-1639 **Thread Direction:** Right-hand and right-hand **Torque Load Rating:** 3222.0 inch-pounds **Key Length:** 1.750 inches **Mounting Type:** Foot **Key Width:** 0.375 inches **Mounting Hole Diameter:** 0.656 inches **Mounting Hole Quantity: Thread Size:** 1.000-11-1/2 and 1.000-11-1/2 **Shaft Diameter:** 1.624 inches **Operating Speed At Rated Capacity In Rpm:** 2500.0 **Drive Shaft Type:** Keyed **Housing Material:** Steel **Screw Thread Series Designator:** Nptf and nptf **Shaft Rotation Direction:** Clockwise and counterclockwise **Thread Location:** Internal and internal **Connection Quantity:** 1 and 1 **Connection Type:** Inlet and outlet **Maximum Working Pressure Rating At Specificationified Tempurature Range:** 5000 psi at minus 160 degrees f to 0 degrees f **Connection Design:** Threaded and threaded **Key Height:**

0.375 inches

Displacement Type:

Constant

NSN 4320-00-360-1639

Hydraulic Motor - Page 2 of 2



Constant Displacement Per Revolution: 4.050 cubic inches Mounting Bolt Hole Spacing: 6.000 in. By 10.000 in. C to c Housing Surface Treatment: Enameled Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: T103-f