## NSN 4320-00-362-4518

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-362-4518

Prime Mover Quantity:  1 Prime Mover Cooling Medium: Air Intake Connection Quantity:  1 Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Prime Mover Cooling Medium:  Air Intake Connection Quantity:  Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Air Intake Connection Quantity:  1 Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Intake Connection Quantity:  1 Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Intake Connection Type: Round flange Discharge Connection Quantity:  1 Discharge Connection Type:
Round flange  Discharge Connection Quantity:  1  Discharge Connection Type:
Discharge Connection Quantity:  1  Discharge Connection Type:
1 Discharge Connection Type:
Discharge Connection Type:
-
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils and water, fresh
Environmental Protection:
Dripproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
31.0 gallons per minute
Discharge Pressure:
125.0 pounds per square inch gage
Total Head:
7.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Vane
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Prime Mover Power Rating:
0.083 horsepower
Voltage In Volts:
115.0
Phase:
Single

## NSN 4320-00-362-4518

Rotary Pump Unit - Page 2 of 2



Frequency	In F	lertz:
-----------	------	--------

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400