

View Online at <https://aerobasegroup.com/nsn/4320-00-368-3186>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

180.0 gallons per minute

Total Head:

50.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

7.5

Discharge Connection Thread Size And Series/type Designator:

2.500-7 1/2 nh

Intake Connection Thread Size And Series/type Designator:

2.500-7 1/2 nh

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Controller has magnetic casing, unit will operate in horizontal or any midway position

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400