

View Online at <https://aerobasegroup.com/nsn/4320-00-368-3214>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

16.0 gallons per minute

Discharge Pressure:

150.0 pounds per square inch gage

Operating Speed At Rated Capacity:

850.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

3.3

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400