

View Online at <https://aerobasegroup.com/nsn/4320-00-368-3238>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils or water, salt

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

50.0 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Lobular

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

8.0

**Prime Mover Power Rating:**

5.250 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Furnished with controller

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400