## NSN 4320-00-368-4419

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-368-4419

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Frame
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded external
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded external
Media For Which Designed:
Water, salt
Pump Quantity:
1
Maximum Discharge Flow Rate:
250.0 gallons per minute
Discharge Pressure:
100.0 pounds per square inch gage
Total Head:
224.000 feet
Suction Lift:
16.000 feet
Operating Speed At Rated Capacity:
4500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Double
Prime Mover Type:
Gasoline engine
Discharge Connection Thread Size And Series/type Designator:
2.500-7-1/2 nh

## NSN 4320-00-368-4419

Centrifugal Pump Unit - Page 2 of 2



Intake Connection	Thread S	Size And	Series/type	Designator:
-------------------	----------	----------	-------------	-------------

3.000-6 nh

**Features Provided:** 

Self-priming

**Prime Mover Power Rating:** 

25.000 horsepower

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400