Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-369-9776

_			
	me Mover Quantity:		
1			
	me Mover Cooling Medium:		
Ai			
	ige Quantity:		
1			
	ake Connection Quantity:		
1			
	ake Connection Type:		
	und flange		
D	charge Connection Quantity:		
1			
	charge Connection Type:		
	und flange		
	rrent Type:		
A			
	dia For Which Designed:		
	iter, salt		
E	vironmental Protection:		
	pproof		
P	mp Quantity:		
1			
C	oling Method:		
S	f ventilated		
Μ	ximum Discharge Flow Rate:		
53	00.0 gallons per minute		
Т	tal Head:		
43	000 feet		
0	erating Speed At Rated Capacity:		
11	75.0 revolutions per minute		
P	mping Element Operating Position:		
Ve	rtical		
C	ntrifugal Pump Design:		
R	dial flow		
C	ntrifugal Pump Impeller Quantity:		
1			
C	ntrifugal Pump Impeller Suction Type:		
Si	gle		
P	me Mover Type:		
EI	ctric motor		
In	losure Type:		
Pa	rtially enclosed		

NSN 4320-00-369-9776

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:

93.0

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Quality controlled in accordance with navships 0948-045-7010material identification and control instructions for level 1/sub-safeitems, left hand unit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400