

View Online at <https://aerobasegroup.com/nsn/4320-00-371-7632>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

115.0 gallons per minute

Total Head:

25.000 feet

Suction Lift:

10.000 feet

Operating Speed At Rated Capacity:

2200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Gasoline engine

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

3.100 horsepower

Reference Number Differentiating Characteristics:

As differentiated by mounting type requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400