## NSN 4320-00-375-1851

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-375-1851

| Prime Mover Quantity:                   |
|---|
| 1                                       |
| Prime Mover Cooling Medium:             |
| Air                                     |
| Stage Quantity:                         |
| 1                                       |
| Intake Connection Quantity:             |
| 1                                       |
| Intake Connection Type:                 |
| Round flange                            |
| Discharge Connection Quantity:          |
| 1                                       |
| Discharge Connection Type:              |
| Round flange                            |
| Current Type:                           |
| Dc                                      |
| Media For Which Designed:               |
| Water, fresh                            |
| Environmental Protection:               |
| Dripproof                               |
| Pump Quantity:                          |
| 1                                       |
| Cooling Method:                         |
| Self ventilated                         |
| Maximum Discharge Flow Rate:            |
| 350.0 gallons per minute                |
| Total Head:                             |
| 32.000 feet                             |
| Suction Lift:                           |
| 4.000 feet                              |
| Operating Speed At Rated Capacity:      |
| 1750.0 revolutions per minute           |
| Pumping Element Operating Position:     |
| Vertical                                |
| Centrifugal Pump Design:                |
| Radial flow                             |
| Centrifugal Pump Impeller Quantity:     |
| 1                                       |
| Centrifugal Pump Impeller Suction Type: |
| Single                                  |
| Prime Mover Type:                       |
| Electric motor                          |

## NSN 4320-00-375-1851

Centrifugal Pump Unit - Page 2 of 2



| Inclosure Type:           |
|---------------------------|
| Partially enclosed        |
| Current Rating In Amps:   |
| 21.8                      |
| Prime Mover Power Rating: |
| 5.500 horsepower          |
| Voltage In Volts:         |
| 250.0                     |
| Special Features:         |
| Ccw rotation              |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |

No Fiig: A19400