

View Online at <https://aerobasegroup.com/nsn/4320-00-375-1852>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

350.0 gallons per minute

Total Head:

32.000 feet

Suction Lift:

4.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

21.8

Prime Mover Power Rating:

5.500 horsepower

Voltage In Volts:

250.0

Special Features:

Cw rotation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400