

View Online at <https://aerobasegroup.com/nsn/4320-00-375-1865>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Round flange

Discharge Connection Quantity:

2

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Oil and water, salt

Environmental Protection:

Splash proof

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

70.0 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Total Head:

28.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute and 420.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

15.2

Prime Mover Power Rating:

9.0 horsepower

Voltage In Volts:

440.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400