

View Online at <https://aerobasegroup.com/nsn/4320-00-376-1505>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Splashtight

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

35.0 gallons per minute

**Discharge Pressure:**

40.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1150.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

4.5

**Prime Mover Power Rating:**

3.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Provided w/controller

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400