

View Online at <https://aerobasegroup.com/nsn/4320-00-389-4907>

Prime Mover Quantity:

1

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Pump Quantity:

1

Maximum Discharge Flow Rate:

1670.0 gallons per minute

Discharge Pressure:

70.0 pounds per square inch gage

Operating Speed At Rated Capacity:

900.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Current Rating In Amps:

74.7

Prime Mover Power Rating:

50.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by prime mover type requirement, electric motor mfr general dynamics corporation electro dynamics div avenel operations
dwg no. 3504-11

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400