

View Online at <https://aerobasegroup.com/nsn/4320-00-389-4907>

**Prime Mover Quantity:**

1

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

1670.0 gallons per minute

**Discharge Pressure:**

70.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

900.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Current Rating In Amps:**

74.7

**Prime Mover Power Rating:**

50.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by prime mover type requirement, electric motor mfr general dynamics corporation electro dynamics div avenel operations  
dwg no. 3504-11

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A19400