NSN 4320-00-400-6381

Hydraulic Motor - Page 1 of 2

Thread Direction:

Torque Load Rating:

Right-hand



View Online at https://aerobasegroup.com/nsn/4320-00-400-6381

1600.0 inch-pounds
Mounting Type:
Flange
Keyway Width:
0.187 inches
Keyway Depth:
0.094 inches
Mounting Hole Diameter:
0.560 inches
Mounting Hole Quantity:
2
Thread Size:
0.250-18
Shaft Diameter:
Between 0.874 inches and 0.875 inches
Bolt Hole Quantity:
4 and 4
Operating Speed At Rated Capacity In Rpm:
3000.0
Mounting Bolt Circle Diameter:
5.750 inches
Keyway Length:
1.250 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Steel
Screw Thread Series Designator:
Npt
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal
Shaft Protrusion Length:
1.880 inches
Connection Quantity:
1 and 1 and 1
Tana Tana T
Connection Type:

NSN 4320-00-400-6381

Hydraulic Motor - Page 2 of 2

Fiig: T103-f



Maximum Working Pressure Rating At Specificationified Tempurature Range: 2500ps1 at plus 120 degrees f **Connection Design:** Flanged and flanged and threaded **Bolt Hole Thread Size:** 0.438-14 and 0.438-14 **Displacement Type:** Constant **Constant Displacement Per Revolution:** 4.190 cubic inches **Bolt Hole Spacing:** 1.187 in. By 2.312 in. Shelf Life: N/a **Unit Of Measure:** Demilitarization: No