

View Online at <https://aerobasegroup.com/nsn/4320-00-406-0083>

**Intake Connection Quantity:**

3

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

3

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

45.0 gallons per minute and 9.5 gallons per minute and 4.0 gallons per minute

**Discharge Pressure:**

60.0 pounds per square inch gage and 30.0 pounds per square inch gage

**Suction Lift:**

6.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

Key type, internal

**Drive Shaft Length:**

Between 0.910 inches and 0.940 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 unf and 1.875-12 unf and 0.750-16 unf

**Intake Connection Thread Size And Series/type Designator:**

1.062-12 unf and 1.875-12 unf and 0.750-16 unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A19400