## NSN 4320-00-407-8730

Rotary Pump - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4320-00-407-8730



Intake Connection Quantity:

2

Intake Connection Type:

Rectangular flange and threaded internal

## **Discharge Connection Quantity:**

2

#### **Discharge Connection Type:**

Rectangular flange and threaded internal

#### **Drive Connection Type:**

Close coupled

#### Media For Which Designed:

Hydrocarbon fuels and oils

#### **End Application:**

Excavator, model tprps-tr

#### Maximum Discharge Flow Rate:

53.0 gallons per minute and 22.0 gallons per minute

#### **Discharge Pressure:**

2000.0 pounds per square inch gage and 2000.0 pounds per square inch gage

#### **Operating Speed At Rated Capacity:**

2000.0 revolutions per minute and 2000.0 revolutions per minute

### **Pumping Element Operating Position:**

Horizontal

#### Pump Rotation Direction:

Counterclockwise

#### Rotary Pump Design:

Gear

#### **Operation Method:**

Powered

#### Drive Shaft Type:

Key type, external

#### Drive Shaft End Diameter:

1.250 inches

#### Drive Shaft Length:

1.940 inches

#### Discharge Connection Thread Size And Series/type Designator:

1.000-14 npt

#### Intake Connection Thread Size And Series/type Designator:

0.750-14 npt

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4320-00-407-8730

Rotary Pump - Page 2 of 2

Demilitarization:

No

Fiig:

A19400

