

View Online at <https://aerobasegroup.com/nsn/4320-00-419-3199>

Prime Mover Quantity:

2

Mounting Type:

Base

Stage Quantity:

1 and 1

Intake Connection Quantity:

2

Intake Connection Type:

Round flange and round flange

Discharge Connection Quantity:

2

Discharge Connection Type:

Round flange and round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Waterproof

Pump Quantity:

2

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

170.0 gallons per minute and 170.0 gallons per minute

Discharge Pressure:

45.0 pounds per square inch gage and 45.0 pounds per square inch gage

Total Head:

101.000 feet and 101.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute and 3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Independent

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

12.7

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400