

View Online at <https://aerobasegroup.com/nsn/4320-00-419-3199>

**Prime Mover Quantity:**

2

**Mounting Type:**

Base

**Stage Quantity:**

1 and 1

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Round flange and round flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Round flange and round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, salt

**Environmental Protection:**

Waterproof

**Pump Quantity:**

2

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

170.0 gallons per minute and 170.0 gallons per minute

**Discharge Pressure:**

45.0 pounds per square inch gage and 45.0 pounds per square inch gage

**Total Head:**

101.000 feet and 101.000 feet

**Operating Speed At Rated Capacity:**

3600.0 revolutions per minute and 3600.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Independent

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

12.7

**Features Provided:**

Self-priming

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400