## NSN 4320-00-420-4841

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-420-4841

Intake Connection Type: Threaded internal Discharge Connection Quantity:  1 Discharge Connection Type: Threaded internal Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Threaded internal  Discharge Connection Quantity:  1  Discharge Connection Type: Threaded internal  Media For Which Designed: Hydrocarbon fuels and oils  Maximum Discharge Flow Rate: 4.1 gallons per minute  Discharge Pressure: 20.0 pounds per square inch gage  Total Head: 36.000 feet  Operating Speed At Rated Capacity: 500.0 revolutions per minute  Pumping Element Operating Position: Horizontal  Pump Rotation Direction: Counterclockwise  Rotary Pump Design: Gear  Operation Method: Powered  Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt  Intake Connection Thread Size And Series/type Designator: 0.500-14 npt  Shelf Life:
Discharge Connection Quantity:  1 Discharge Connection Type: Threaded internal Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Discharge Connection Type: Threaded internal Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Discharge Connection Type: Threaded internal Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Threaded internal  Media For Which Designed: Hydrocarbon fuels and oils  Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Media For Which Designed: Hydrocarbon fuels and oils Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Hydrocarbon fuels and oils  Maximum Discharge Flow Rate: 4.1 gallons per minute  Discharge Pressure: 20.0 pounds per square inch gage  Total Head: 36.000 feet  Operating Speed At Rated Capacity: 500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt  Intake Connection Thread Size And Series/type Designator: 0.500-14 npt  Shelf Life:
Maximum Discharge Flow Rate: 4.1 gallons per minute Discharge Pressure: 20.0 pounds per square inch gage Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
4.1 gallons per minute  Discharge Pressure:  20.0 pounds per square inch gage  Total Head:  36.000 feet  Operating Speed At Rated Capacity:  500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Discharge Pressure:  20.0 pounds per square inch gage  Total Head:  36.000 feet  Operating Speed At Rated Capacity:  500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Total Head: 36.000 feet Operating Speed At Rated Capacity: 500.0 revolutions per minute Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Total Head: 36.000 feet  Operating Speed At Rated Capacity: 500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt  Intake Connection Thread Size And Series/type Designator: 0.500-14 npt  Shelf Life:
36.000 feet  Operating Speed At Rated Capacity: 500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Operating Speed At Rated Capacity: 500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt  Intake Connection Thread Size And Series/type Designator: 0.500-14 npt  Shelf Life:
500.0 revolutions per minute  Pumping Element Operating Position:  Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Pumping Element Operating Position: Horizontal Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Horizontal  Pump Rotation Direction:  Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Pump Rotation Direction: Counterclockwise Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Counterclockwise  Rotary Pump Design:  Gear  Operation Method:  Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt  Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
Rotary Pump Design: Gear Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Operation Method: Powered Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Operation Method: Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt Intake Connection Thread Size And Series/type Designator:  0.500-14 npt Shelf Life:
Powered  Discharge Connection Thread Size And Series/type Designator:  0.500-14 npt Intake Connection Thread Size And Series/type Designator:  0.500-14 npt Shelf Life:
Discharge Connection Thread Size And Series/type Designator: 0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
0.500-14 npt Intake Connection Thread Size And Series/type Designator: 0.500-14 npt Shelf Life:
Intake Connection Thread Size And Series/type Designator:  0.500-14 npt  Shelf Life:
0.500-14 npt Shelf Life:
Shelf Life:
N/
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400