

View Online at <https://aerobasegroup.com/nsn/4320-00-424-3891>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

61.6 gallons per minute

**Total Head:**

5.000 feet

**Suction Lift:**

2.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

6.2 and 3.1

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Submersible inlet with strainer

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by electric requirement

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400