## NSN 4320-00-428-7982

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-428-7982

Prime Mover Quantity:
1
Prime Mover Cooling Medium:  Air
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
45.0 gallons per minute
Discharge Pressure:
3000.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1800.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Rotary Pump Design:
Screw
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Current Rating In Amps:
120.0
Prime Mover Power Rating:
100.000 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0

## NSN 4320-00-428-7982

Rotary Pump Unit - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400