

View Online at <https://aerobasegroup.com/nsn/4320-00-435-7948>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

10.0 gallons per minute

**Discharge Pressure:**

25.0 pounds per square inch gage

**Total Head:**

74.000 feet

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

1.8

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Not provided with controller

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

N-2 class and viii type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400