## NSN 4320-00-442-6301

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-442-6301

Prime Mover Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
2
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Environmental Protection:
Dripproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
3.0 gallons per minute
Discharge Pressure:
25.0 pounds per square inch gage
Operating Speed At Rated Capacity:
12000.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Vane
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
0.125-27 npt
Intake Connection Thread Size And Series/type Designator:
0.125-27 npt
Prime Mover Power Rating:
0.013 horsepower
Voltage In Volts:
27.5
Shelf Life:
N/a

## NSN 4320-00-442-6301

Rotary Pump Unit - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A19400