

View Online at <https://aerobasegroup.com/nsn/4320-00-443-5608>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Splashtight

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

500.0 gallons per minute

**Discharge Pressure:**

55.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Rotary Pump Design:**

Screw

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

52.0

**Prime Mover Power Rating:**

40.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Provided with controller

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

li type

**Reference Number Differentiating Characteristics:**

With reliance electric co. Motor dwg. No. 86716

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400