

View Online at <https://aerobasegroup.com/nsn/4320-00-443-5612>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Glycerine or water, fresh

Environmental Protection:

Splashtight

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

153.0 gallons per minute

Discharge Pressure:

88.3 pounds per square inch gage

Total Head:

231.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

26.0

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Provided w/controller

Frequency In Hertz:

60.0

Specification Or Standard:

C-1 class

Reference Number Differentiating Characteristics:

W/reliance elec co. Motor dwg no. 84750

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A19400