NSN 4320-00-444-2489

Rotary Pump Unit - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4320-00-444-2489

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

15.0 gallons per minute

Discharge Pressure:

1100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

31.0

Prime Mover Power Rating:

25.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

NSN 4320-00-444-2489

Rotary Pump Unit - Page 2 of 2

Frequency In Hertz:

60.0

Specification Or Standard:

3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400

