

View Online at <https://aerobasegroup.com/nsn/4320-00-444-9819>

Prime Mover Quantity:

1

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

3.7 gallons per minute

Discharge Pressure:

1000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

6750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.750-14 npt

Intake Connection Thread Size And Series/type Designator:

0.750-14 npt

Prime Mover Power Rating:

3.500 horsepower

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400