NSN 4320-00-446-2334

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-446-2334

Towns Load Before
Torque Load Rating:
150.0 inch-pounds
Key Length:
Shaft extends 1-5/16 in. From housing
Mounting Type:
Face
Mounting Hole Diameter:
0.313 inches
Mounting Hole Quantity:
6
Thread Size:
1/2-14
Shaft Diameter:
3/4 in. Diameter drive shaft
Operating Speed At Rated Capacity In Rpm:
3600.0
Drive Shaft Type:
Keyway
Housing Material:
Iron, cast
Screw Thread Series Designator:
Npt
Thread Location:
Internal
Connection Type:
Inlet and outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
1000 psi
Connection Design:
Threaded
Displacement Type:
Constant
Constant Displacement Per Revolution:
0.960 cubic inches
Mounting Bolt Hole Spacing:
Mounting holes spaced 45 degrees on 3-1/16 in. Bolt circle
Housing Surface Treatment:
Enameled
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4320-00-446-2334 Hydraulic Motor - Page 2 of 2



Demilitarization:

No

Fiig:

T103-f