NSN 4320-00-453-9049

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-453-9049

Thread Direction:
Right-hand
Torque Load Rating:
1600.0 inch-pounds
Mounting Type:
Foot
Keyway Width:
0.187 inches
Keyway Depth:
0.094 inches
Mounting Hole Diameter:
0.680 inches
Mounting Hole Quantity:
4
Thread Size:
0.250-18
Shaft Diameter:
Between 0.874 inches and 0.875 inches
Bolt Hole Quantity:
4 and 4
Operating Speed At Rated Capacity In Rpm:
3000.0
Keyway Length:
1.250 inches
Drive Shaft Type:
Machine keyway
Housing Material:
Steel
Screw Thread Series Designator:
Npt
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal
Shaft Protrusion Length:
1.560 inches
Connection Quantity:
1 and 1 and 1
Connection Type:
Outlet
Maximum Working Pressure Rating At Specificationified Tempurature Range:
2500nci at plus 120 degrees f

2500psi at plus 120 degrees f

NSN 4320-00-453-9049 Hydraulic Motor - Page 2 of 2



Connection Design:
Flanged and flanged and threaded
Bolt Hole Thread Size:
0.438-14 and 0.438-14
Displacement Type:
Constant
Constant Displacement Per Revolution:
4.190 cubic inches
Bolt Hole Spacing:
1.187 in. By 2.312 in.
Mounting Bolt Hole Spacing:
2.000 in. By 5.750 in.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T103-f