

View Online at <https://aerobasegroup.com/nsn/4320-00-453-9729>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

7

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

300.0 gallons per minute

Discharge Pressure:

468.0 pounds per square inch gage

Total Head:

1100.000 feet

Suction Lift:

8.700 feet

Operating Speed At Rated Capacity:

3535.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

7

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Alternate

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

20.0

Features Provided:

Self-priming

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400