

View Online at <https://aerobasegroup.com/nsn/4320-00-453-9748>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

82.0 gallons per minute

Discharge Pressure:

40.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1150.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

7.5

Prime Mover Power Rating:

5.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Not provided with controller

Frequency In Hertz:

60.0

Specification Or Standard:

3 type and 0-1 class

Reference Number Differentiating Characteristics:

As differentiated by reply to pacs acdc, elec and amps

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400