NSN 4320-00-455-1332

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-455-1332

| Landa Carantina Carantin |
|---|
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Unthreaded internal |
| Drive Connection Type: |
| Rigid coupled |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Maximum Discharge Flow Rate: |
| 2.0 gallons per minute |
| Discharge Pressure: |
| 825.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 3600.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Clockwise |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| D-type |
| Drive Shaft Length: |
| 2.000 inches |
| Unpackaged Unit Length: |
| 4.500 inches |
| Unpackaged Unit Width: |
| 2.531 inches |
| Unpackaged Unit Height: |
| 2.531 inches |
| Pump Basic Material: |
| Steel |
| Intake Connection Thread Size And Series/type Designator: |
| 0.125-27 npt |
| Shelf Life: |
| N/a |

NSN 4320-00-455-1332

Rotary Pump - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A19400