NSN 4320-00-473-5150

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-473-5150

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Water, fresh |
| Environmental Protection: |
| Dripproof |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Air to air cooled |
| Maximum Discharge Flow Rate: |
| 5.0 gallons per minute |
| Total Head: |
| 103.900 feet |
| Operating Speed At Rated Capacity: |
| 1750.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Double |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |

NSN 4320-00-473-5150Centrifugal Pump Unit - Page 2 of 2



| Current Rating In Amps: |
|--|
| 7.4 |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.250-11-1/2 npt |
| ntake Connection Thread Size And Series/type Designator: |
| 1.250-11-1/2 npt |
| Features Provided: |
| Self-priming |
| Voltage In Volts: |
| 115.0 |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |
| |