

View Online at <https://aerobasegroup.com/nsn/4320-00-476-5404>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Water, fresh

**Stage Quantity:**

12

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Water cooled

**Maximum Discharge Flow Rate:**

51.0 gallons per minute

**Discharge Pressure:**

60.0 pounds per square inch gage

**Total Head:**

280.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

12

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Prime Mover Power Rating:**

5.000 horsepower

**Voltage In Volts:**

230.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400