

View Online at <https://aerobasegroup.com/nsn/4320-00-476-5404>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Stage Quantity:

12

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

51.0 gallons per minute

Discharge Pressure:

60.0 pounds per square inch gage

Total Head:

280.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

12

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Prime Mover Power Rating:

5.000 horsepower

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400