

View Online at <https://aerobasegroup.com/nsn/4320-00-477-6042>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

105.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Total Head:

23.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Discharge Connection Thread Size And Series/type Designator:

3.000-8 npt

Intake Connection Thread Size And Series/type Designator:

3.000-8 npt

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400