## NSN 4320-00-479-3432

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-479-3432

Prime Mover Quantity:
1
Mounting Type:
Base
Stage Quantity:
1
Exhaust Pressure:
15.0 pounds per square inch gage
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Media For Which Designed:
Water, salt
Power Drive Operating Pressure:
525.0 pounds per square inch gage
Pump Quantity:
1
Maximum Discharge Flow Rate:
400.0 gallons per minute
Total Head:
224.000 feet
Operating Speed At Rated Capacity:
3450.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Double
Prime Mover Type:
Steam turbine
Features Provided:
Self-priming
Reference Number Differentiating Characteristics:
As differentiated by nump material

As differentiated by pump material

## NSN 4320-00-479-3432

Centrifugal Pump Unit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A19400