

View Online at <https://aerobasegroup.com/nsn/4320-00-482-3518>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air and liquid and oil

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Liquid

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

5.3 gallons per minute

Discharge Pressure:

7.5 pounds per square inch gage

Total Head:

15.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

7.000 inches

Unpackaged Unit Width:

4.5000 inches

Unpackaged Unit Height:

5.500 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.2

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

0.066 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

6.0 ft cord w/3-prong molded plug; underwriters laboratories inc. Listed

Frequency In Hertz:

60.0

Supplementary Features:

Aluminum motor housing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400