

View Online at <https://aerobasegroup.com/nsn/4320-00-482-3518>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air and liquid and oil

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

5.3 gallons per minute

**Discharge Pressure:**

7.5 pounds per square inch gage

**Total Head:**

15.000 feet

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

7.000 inches

**Unpackaged Unit Width:**

4.5000 inches

**Unpackaged Unit Height:**

5.500 inches

**Pump Basic Material:**

Plastic

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

3.2

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Prime Mover Power Rating:**

0.066 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

6.0 ft cord w/3-prong molded plug; underwriters laboratories inc. Listed

**Frequency In Hertz:**

60.0

**Supplementary Features:**

Aluminum motor housing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400