

View Online at <https://aerobasegroup.com/nsn/4320-00-483-4655>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

47.0 gallons per minute

**Total Head:**

5.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Length:**

13.500 inches

**Unpackaged Unit Width:**

6.7500 inches

**Unpackaged Unit Height:**

6.750 inches

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

3.2 and 1.6

**Discharge Connection Thread Size And Series/type Designator:**

0.750-14 npt

**Intake Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Prime Mover Power Rating:**

0.5 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Must be mtd below media to be pumped

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A19400