NSN 4320-00-494-9738

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-494-9738

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Water, salt |
| Environmental Protection: |
| Splash proof |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Self ventilated |
| Maximum Discharge Flow Rate: |
| 35.0 gallons per minute |
| Total Head: |
| 79.000 feet |
| Operating Speed At Rated Capacity: |
| 3500.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| |

NSN 4320-00-494-9738

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:

3.3

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Not provided w/controller

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A19400