

View Online at <https://aerobasegroup.com/nsn/4320-00-494-9744>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

2

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Splash proof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Maximum Discharge Flow Rate:**

750.0 gallons per minute

**Total Head:**

166.000 feet

**Operating Speed At Rated Capacity:**

1150.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

75.0

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

E class

**Reference Number Differentiating Characteristics:**

Not provided w/controller

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400