

View Online at <https://aerobasegroup.com/nsn/4320-00-497-5506>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal and threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

4.1 gallons per minute

Discharge Pressure:

5.7 pounds per square inch gage

Total Head:

13.000 feet

Operating Speed At Rated Capacity:

3000.0 revolutions per minute

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.1

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

250.0 watts

Voltage In Volts:

230.0

Phase:

Single

Frequency In Hertz:

50.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400